

# BELGRADO 2

SERVE-OVER & SEMI-VERTICAL • REMOTE REFRIGERATION UNIT & PLUG-IN



**arneg**

ITALIA


YOUR GLOBAL PARTNER FOR RETAIL SOLUTIONS

**BELGRADO 2 VETR TN V LINEARE R**


Length without side panels	mm		<b>937</b>	<b>1250</b>	<b>1875</b>	<b>2500</b>	<b>3125</b>	<b>3750</b>	
Temperature class		3 M1	•	•	•	•	•	•	
		3 M2	•	•	•	•	•	•	
		0/+2	•	•	•	•	•	•	
Preservation temperature	°C	+2/+4	•	•	•	•	•	•	
Horizontal display area*	m <sup>2</sup>	Depth	70	-	-	1,31	1,75	2,19	2,63
			80	0,75	1	1,5	2	2,5	3
			90	0,84	1,13	1,69	2,25	2,81	3,38
Energy class**	Depth	70	-	-					
		80-90							

**BELGRADO 2 VETR TN V LINEARE R 83**


Length without side panels	mm		<b>625</b>	<b>1250</b>	<b>1875</b>	<b>2500</b>	<b>3125</b>	<b>3750</b>
Temperature class		3 M0	•	•	•	•	•	•
		3 M1	•	•	•	•	•	•
		3 M2	•	•	•	•	•	•
Preservation temperature	°C	-1/+1	•	•	•	•	•	•
		0/+2	•	•	•	•	•	•
		+2/+4	•	•	•	•	•	•
Horizontal display area*	m <sup>2</sup>		0,52	1,04	1,56	2,08	2,59	3,11
Energy class**								




**SELF 70**




**SELF 80**




**SELF 83**




**SELF 90**




**TOPSELF 70**




**TOPSELF 80**




**TOPSELF 83**




**TOPSELF 90**




**VDA 70**



**VDA 80**







**VDA 83**



**VDA 90**

\*Value referred to illustrated configurations.

\*\*The energy class may vary depending on the product configuration.





**VDL 70**  
**BELGRADO 2 VETR BT V LINEARE R**

**VDL 80**

**VDL 83**

**VDL 90**

Length without side panels	mm	<b>1250</b>	<b>1875</b>	<b>2500</b>	<b>3750</b>
Temperature class	3L3	•	•	•	•
Preservation temperature	°C -18/-21	•	•	•	•
Horizontal display area*	m <sup>2</sup>	1,05	1,58	2,1	3,15
Energy class**		<b>A</b> <b>F</b>	<b>A</b> <b>F</b>	<b>A</b> <b>F</b>	<b>A</b> <b>F</b>





**SELF 90**  
**BELGRADO 2 VETR-FH TN S LINEARE R**

**VDA 90**

Length without side panels	mm	<b>1250</b>	<b>1875</b>	<b>2500</b>	<b>3125</b>	<b>3750</b>
Temperature class	3 M1	•	•	•	•	•
Preservation temperature	°C 0/+2	•	•	•	•	•
Horizontal display area*	m <sup>2</sup>	1,02	1,53	2,04	2,55	3,05

Model not subject to energy labelling.






**SELF 90**  
**BELGRADO 2 VETR-BM TC LINEARE**

**VDA 90**

Length without side panels	mm	<b>625</b>	<b>937</b>	<b>1250</b>
Stored product temperature	°C +65	•	•	•
Horizontal display area*	m <sup>2</sup>	Depth 80	-	0,4
		90	0,32	0,54

Model not subject to energy labelling.



**VDA 80**  
\*Value referred to illustrated configurations.

**VDA 90**


**VDL 80**

\*\*The energy class may vary depending on the product configuration.


**BELGRADO 2 VETR-PW TC LINEARE**

Length without side panels	mm		<b>625</b>	<b>937</b>	<b>1250</b>
Stored product temperature	°C	+65	•	•	•
Horizontal display area*	m <sup>2</sup>	Depth	80	-	0,4
			90	0,32	1,25


Model not subject to energy labelling.




**VDA 80**



**VDA 90**




**VDL 80**




**VDL 90**

**BELGRADO 2 VETR-CK TN V LINEARE R**


Length without side panels	mm		<b>1250</b>	<b>1875</b>	<b>2500</b>
Temperature class		3M2	•	•	•
Preservation temperature	°C	+2/ +4	•	•	•
Horizontal display area*	m <sup>2</sup>	Depth	70	-	1,31
			80	1,5	-
			90	1,13	1,69
Energy class**	Depth	70	-	<b>F</b>	<b>F</b>
		80	<b>F</b>	-	-
		90	<b>F</b>	<b>F</b>	<b>F</b>




**VDA 70**




**VDA 80**




**VDA 90**



**VDL 70**



**VDL 80**



**VDL 90**


\*Value referred to illustrated configurations.

\*\*The energy class may vary depending on the product configuration.

### BELGRADO 2 VETR-BD DRY LINEARE

Length without side panels	mm	<b>1250</b>	<b>1875</b>	<b>2500</b>	<b>3750</b>
Horizontal display area*	m <sup>2</sup>	-	-	-	-


Model not subject to energy labelling.



**VDA 90**

### BELGRADO 2 VETR TN V LINEARE R TH

Length without side panels	mm	<b>937</b>	<b>1250</b>
Temperature class	3 M1	•	•
	3 M2	•	•
Preservation temperature	°C 0/+2	•	•
	+2/+4	•	•
Horizontal display area*	m <sup>2</sup>	1,18	1,57
Energy class**		<b>F</b>	<b>F</b>




**TH 90**


### BELGRADO 2 VETR-PW TC LINEARE TH

Length without side panels	mm	<b>937</b>	<b>1250</b>
Stored product temperature	°C	+65	•
Horizontal display area*	m <sup>2</sup>	Depth 80	-
		90	1,25
		1,71	1,71

Model not subject to energy labelling.



**TH 80**



**TH 90**

\*Value referred to illustrated configurations.


\*\*The energy class may vary depending on the product configuration.

**BELGRADO 2 SVT-A-1 TN V LINEARE R**


Length without side panels	mm	937		1250		1875			2500			3125		3750		
Height	cm	125	150	125	150	114	125	150	114	125	150	125	150	125	150	
Temperature class	3M1	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
	3M2	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Preservation temperature	0/+2	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
	+2/+4	•	•	•	•	•	•	•	•	•	•	•	•	•	•	
Horizontal display area*	m <sup>2</sup>	Depth	70	-	1,35	-	-	-	-	2,7	-	-	-	4,05	-	
			80	-	1,48	1,85	-	2,22	2,78	-	2,96	3,71	4,43	-	-	5,58
			90	1,2	1,67	1,6	2,23	2,4	3,34	3,21	4,46	4,01	5,57	4,81	6,68	
Energy class**	Depth	70	-	A ↑ G E	-	-	-	-	A ↑ G E	-	-	-	A ↑ G E	-		
		80	-	A ↑ G E	-	A ↑ G E	-	A ↑ G E	A ↑ G E	A ↑ G E	-	-	A ↑ G E			
		90	A ↑ G E	A ↑ G E	A ↑ G E	A ↑ G E	A ↑ G E	A ↑ G E	A ↑ G E	A ↑ G E	A ↑ G E					

\*Value referred to illustrated configurations.


\*\*The energy class may vary depending on the product configuration.




**70 H125**




**70 H150**




**80 H114**




**80 H125**




**80 H150**



**90 H114**



**90 H125**




**90 H150**

**BELGRADO 2 SVT-A-1 TN V TESTATA R**


Overall length	mm	<b>1875</b>	
Height	cm	<b>125</b>	<b>150</b>
Temperature class	3M1	•	•
	3M2	•	•
Preservation temperature	°C	0/+2	•
		+2/+4	•
Horizontal display area*	m <sup>2</sup>	Depth 80	-
		90	2,4
Energy class**	Depth	80	
		90	-

\*Value referred to illustrated configurations.

\*\*The energy class may vary depending on the product configuration.



**80 H150**



**90 H125**